



Nero Collection

Indoor Lighting

ACUMEN

www.acumenlight.com

NERO COLLECTION




Nero Black Hole

This lighting solution is engineered to precisely focus light and distribute it evenly, ensuring both functional and aesthetic illumination. Featuring a small aperture design combined with cross-lighting technology, it minimizes direct glare while enhancing ambient brightness. The fixture delivers low glare performance and boasts high luminous efficiency, reaching up to 70%, making it an ideal choice for energy-efficient and visually comfortable lighting applications.

Nero FLAT

ACU FS 251101




Wattage	Beam Angle
5W	15° 36°
Color Temperature	Lumen Output
3000k	300 Lm
Installation	Rated Life Hours
Recessed	30,000 - 50,000H
CRI	Colors
≥90	■ Black □ White
Input Voltage	Material
220V AC (Via the Attached Remote Driver)	Powder Coated Aluminum
Cutting Section	
Cut out Ø35 mm	



Flat Shape Frame

Nero Collection

ACU FS 251102



Wattage

10W

Beam Angle

15° 36°

Color Temperature

3000k

Lumen Output

600 Lm

Installation

Recessed

Rated Life Hours

30,000 - 50,000H

CRI

≥90

Colors

■ Black □ White

Input Voltage

220V AC
(Via the Attached Remote Driver)

Material


Powder Coated
Aluminum

Cutting Section

Cut out Ø65 mm



ACU FS 251103



Wattage

5W

Beam Angle

15° 36°

Color Temperature

3000k

Lumen Output

900 Lm

Installation

Recessed

Rated Life Hours

30,000 - 50,000H

CRI

≥90

Colors

■ Black □ White

Input Voltage

220V AC
(Via the Attached Remote Driver)

Material

Powder Coated
Aluminum

Cutting Section

Cut out Ø75 mm








Nero **CURVED**

Adjustable Curved Shape Frame

Nero Collection


ACU CS 251000



Wattage	Beam Angle
5W	25° 40°
Color Temperature	Lumen Output
3000k	172 Lm
Installation	Rated Life Hours
Recessed	30,000 - 50,000H
CRI	Colors
≥95	■ Black □ White
Input Voltage	Material
220V AC (Via the Attached Remote Driver)	Powder Coated Aluminum
Cutting Section	
Cut out Ø35 mm	



ACU CS 251001




Wattage	Beam Angle
5W	15° 36°
Color Temperature	Lumen Output
3000k	300 Lm
Installation	Rated Life Hours
Recessed	30,000 - 50,000H
CRI	Colors
≥90	■ Black □ White
Input Voltage	Material
220V AC (Via the Attached Remote Driver)	Powder Coated Aluminum
Cutting Section	
Cut out Ø35 mm	



Adjustable Curved Shape Frame

Nero Collection

ACU CS 251002



Wattage	Beam Angle
---------	------------

10W	15° 36°
-----	---------

Color Temperature	Lumen Output
-------------------	--------------

3000k	600 Lm
-------	--------

Installation	Rated Life Hours
--------------	------------------

Recessed	30,000 - 50,000H
----------	------------------

CRI	Colors
-----	--------

≥95	■ Black □ White
-----	-----------------

Input Voltage	Material
---------------	----------


220V AC (Via the Attached Remote Driver)	Powder Coated Aluminum
---	------------------------

Cutting Section

Cut out Ø85 mm



ACU CS 251003



Wattage	Beam Angle
---------	------------

15W	15° 36°
-----	---------

Color Temperature	Lumen Output
-------------------	--------------

3000k	900 Lm
-------	--------

Installation	Rated Life Hours
--------------	------------------

Recessed	30,000 - 50,000H
----------	------------------

CRI	Colors
-----	--------

≥90	■ Black □ White
-----	-----------------

Input Voltage	Material
---------------	----------

220V AC (Via the Attached Remote Driver)	Powder Coated Aluminum
---	------------------------

Cutting Section

Cut out Ø75 mm






Nero TRIMLESS



ACU TS 251201




Wattage	Beam Angle
5W	15° 36°
Color Temperature	Lumen Output
3000k	350 Lm
Installation	Rated Life Hours
Recessed	30,000 - 50,000H
CRI	Colors
≥90	■ Black □ White
Input Voltage	Material
220V AC (Via the Attached Remote Driver)	Powder Coated Aluminum
Cutting Section	
Cut out Ø35mm	



Nero Trimless Frame

Nero Collection

ACU TS 251202



Wattage	Beam Angle
---------	------------

10W	15° 36°
-----	---------

Color Temperature	Lumen Output
-------------------	--------------

3000k	700 Lm
-------	--------

Installation	Rated Life Hours
--------------	------------------

Recessed	30,000 - 50,000H
----------	------------------

CRI	Colors
-----	--------

≥95	<input checked="" type="checkbox"/> Black <input type="checkbox"/> White
-----	--

Input Voltage	Material
---------------	----------


220V AC (Via the Attached Remote Driver)	Powder Coated Aluminum
---	------------------------

Cutting Section

Cut out Ø45 mm



ACU TS 251203



Wattage	Beam Angle
---------	------------

15W	15° 36°
-----	---------

Color Temperature	Lumen Output
-------------------	--------------

3000k	1050 Lm
-------	---------

Installation	Rated Life Hours
--------------	------------------

Recessed	30,000 - 50,000H
----------	------------------

CRI	Colors
-----	--------

≥90	<input checked="" type="checkbox"/> Black <input type="checkbox"/> White
-----	--

Input Voltage	Material
---------------	----------

220V AC (Via the Attached Remote Driver)	Powder Coated Aluminum
---	------------------------

Cutting Section


Cut out Ø45 mm





Nero WALL WASHER

ACU WW 251301



Wattage	Beam Angle
5W	15° 38°
Color Temperature	Lumen Output
3000k	350 Lm
Installation	Rated Life Hours
Recessed	30,000 - 50,000H
CRI	Colors
≥95	■ Black □ White
Input Voltage	Material
220V AC (Via the Attached Remote Driver)	Powder Coated Aluminum
Cutting Section	
Cut out Ø35mm	



