

www.acumenlight.com

ACUMEN

INDOOR LINEAR CATALOGUE

CATA
LOGUE
Indoor
Linear

INDOOR LINEAR
Honeycomb Diffuser

Honey Comb Louver

Indoor Linear

ACU IL 240101SM



Wattage	Beam angle
34W	60°x75°
Color Temperature	Lumen Output
3000k	2085Lm
4000k	2195Lm
Installation	Rated life hours
Surface Mounted	30,000 - 50,000H
CRI	Colors
≥90	■ Black
Power	
220V AC	

ACU IL 240102SM



Wattage	Beam angle
46W	60°x75°
Color Temperature	Lumen Output
3000k	2820Lm
4000k	2965Lm
Installation	Rated life hours
Surface Mounted	30,000 - 50,000H
CRI	Colors
≥90	■ Black
Power	
220V AC	

ACU IL 240103SM



Wattage	Beam angle
51W	60°x75°
Color Temperature	Lumen Output
3000k	3125Lm
4000k	3290Lm
Installation	Rated life hours
Surface Mounted	30,000 - 50,000H
CRI	Colors
≥90	■ Black
Power	
220V AC	



ACU IL 240104SM




Wattage	Beam angle
68W	60°x75°
Color Temperature	Lumen Output
3000K	4165Lm
4000K	4385Lm
Installation	Rated life hours
Surface Mounted	30,000 - 50,000H
CRI	Colors
≥90	■ Black
Power	
220V AC	

INDOOR LINEAR
Louver Diffuser

Louver

Indoor Linear

ACU IL 240201SM





Wattage	Beam angle
34W	72°
Color Temperature	Lumen Output
3000k	1760Lm
4000k	1890Lm
Installation	Rated life hours
Surface Mounted	30,000 - 50,000H
CRI	Colors
≥90	■ Black
Power	
220V AC	

ACU IL 240202SM



Wattage	Beam angle
51W	72°
Color Temperature	Lumen Output
3000k	2690Lm
4000k	2830Lm
Installation	Rated life hours
Surface Mounted	30,000 - 50,000H
CRI	Colors
≥90	■ Black
Power	
220V AC	

ACU IL 240203SM




Wattage	Beam angle
68W	72°
Color Temperature	Lumen Output
3000k	3550Lm
4000k	3770Lm
Installation	Rated life hours
Surface Mounted	30,000 - 50,000H
CRI	Colors
≥90	■ Black
Power	
220V AC	

INDOOR LINEAR
Prismatic Diffuser

Diffuser

Indoor Linear

ACU IL 240301SM





Wattage	Beam angle
28W	65°x70°
Color Temperature	Lumen Output
3000k	2745Lm
4000k	2890Lm
Installation	Rated life hours
Surface Mounted	30,000 - 50,000H
CRI	Colors
≥90	■ Black
Power	
220V AC	

ACU IL 240302SM



Wattage	Beam angle
34W	65°x70°
Color Temperature	Lumen Output
3000k	3335Lm
4000k	3510Lm
Installation	Rated life hours
Surface Mounted	30,000 - 50,000H
CRI	Colors
≥90	■ Black
Power	
220V AC	

ACU IL 240303SM



Wattage	Beam angle
40W	65°x70°
Color Temperature	Lumen Output
3000k	3920Lm
4000k	4130Lm
Installation	Rated life hours
Surface Mounted	30,000 – 50,000H
CRI	Colors
≥90	■ Black
Power	
220V AC	


INDOOR LINEAR
Recessed



Recessed

Indoor Linear

ACU IL 240401R




Wattage	Beam angle
19W	110°
Color Temperature	Lumen Output
3000k	1900Lm
4000k	2020Lm
Installation	Rated life hours
Recessed	30,000 - 50,000H
CRI	Colors
≥90	■ Black
Power	
220V AC	

ACU IL 240402R



Wattage	Beam angle
27W	110°
Color Temperature	Lumen Output
3000k	2700Lm
4000k	2870Lm
Installation	Rated life hours
Recessed	30,000 - 50,000H
CRI	Colors
≥90	■ Black
Power	
220V AC	

ACU IL 240403R




Wattage	Beam angle
38W	110°
Color Temperature	Lumen Output
3000k	3800Lm
4000k	4040Lm
Installation	Rated life hours
Recessed	30,000 - 50,000H
CRI	Colors
≥90	■ Black
Power	
220V AC	

ACU IL 240404R



Wattage	Beam angle
27W	110°
Color Temperature	Lumen Output
3000k	2800Lm
4000k	2980Lm
Installation	Rated life hours
Recessed	30,000 - 50,000H
CRI	Colors
≥90	■ Black
Power	
220V AC	

ACU IL 240405R



Wattage	Beam angle
---------	------------

38W	110°
-----	------

Color Temperature	Lumen Output
-------------------	--------------

3000k	3950Lm
4000k	4200Lm

Installation	Rated life hours
--------------	------------------

Recessed	30,000 - 50,000H
----------	------------------


CRI	Colors
-----	--------

≥90	■ Black
-----	---------

Power

220V AC

ACU IL 240406R



Wattage	Beam angle
---------	------------

53W	110°
-----	------

Color Temperature	Lumen Output
-------------------	--------------

3000k	5510Lm
4000k	5860Lm

Installation	Rated life hours
--------------	------------------

Recessed	30,000 - 50,000H
----------	------------------


CRI	Colors
-----	--------

≥90	■ Black
-----	---------

Power


220V AC

ACU IL 240407R




Wattage	Beam angle
38W	110°
Color Temperature	Lumen Output
3000k	3950Lm
4000k	4200Lm
Installation	Rated life hours
Recessed	30,000 - 50,000H
CRI	Colors
≥90	■ Black
Power	
220V AC	

ACU IL 240408R



Wattage	Beam angle
60W	110°
Color Temperature	Lumen Output
3000k	6230Lm
4000k	6630Lm
Installation	Rated life hours
Recessed	30,000 - 50,000H
CRI	Colors
≥90	■ Black
Power	
220V AC	

ACU IL 240409R



Wattage	Beam angle
75W	110°
Color Temperature	Lumen Output
3000k	7790Lm
4000k	8290Lm
Installation	Rated life hours
Recessed	30,000 - 50,000H
CRI	Colors
≥90	■ Black
Power	
220V AC	



    @acumenlight
www.acumenlight.com