



MENSA PLUS

Indoor Lighting


ACUMEN

www.acumenlight.com

MENSA PLUS Adjustable spotlight is designed for sophisticated accent lighting perfectly highlighting art, textures, and architectural beauty. A seamless blend of form and function for discerning interiors.

RECESSED ADJUSTABLE SPOT LIGHT


ACU RL 245010



Wattage	Beam Angle
7W	15° 24° 38°
Color Temperature	Lumen Output
3000k	531 Lm
Installation	Rated Life Hours
Recessed	30,000 - 50,000H
CRI	Colors
≥90	■ Black □ White
Input Voltage	Material
220V AC (Via the External Attached Driver)	Powder Coated Aluminum.

RECESSED SPOT LIGHT


ACU RL 245011



Wattage	Beam Angle
15W	15° 24° 38°
Color Temperature	Lumen Output
3000k	1272 Lm
Installation	Rated Life Hours
Recessed	30,000 - 50,000H
CRI	Colors
≥90	■ Black □ White
Input Voltage	Material
220V AC (Via the External Attached Driver)	Powder Coated Aluminum.

RECESSED SPOT LIGHT

ACU RL 245012




Wattage	Beam Angle
24W	15° 24° 38°
Color Temperature	Lumen Output
3000k	2117 Lm
Installation	Rated Life Hours
Recessed	30,000 - 50,000H
CRI	Colors
≥90	■ Black □ White
Input Voltage	Material
220V AC (Via the External Attached Driver)	Powder Coated Aluminum.



SURFACE MOUNTED ADJUSTABLE SPOT LIGHT


ACU SML 245510



Wattage	Beam Angle
7W	15° 24° 38°
Color Temperature	Lumen Output
3000k	531 Lm
Installation	Rated Life Hours
Surface Mounted	30,000 - 50,000H
CRI	Colors
≥90	■ Black □ White
Input Voltage	Material
220V AC (Via the Built In Driver)	Powder Coated Aluminum.

SURFACE MOUNTED SPOT LIGHT


ACU SML 245511



Wattage	Beam Angle
15W	15° 24° 38°
Color Temperature	Lumen Output
3000k	1272 Lm
Installation	Rated Life Hours
Surface Mounted	30,000 - 50,000H
CRI	Colors
≥90	■ Black □ White
Input Voltage	Material
220V AC (Via the Built In Driver)	Powder Coated Aluminum.

SURFACE MOUNTED SPOT LIGHT


ACU SML 245512



Wattage	Beam Angle
24W	15° 24° 38°
Color Temperature	Lumen Output
3000k	2117 Lm
Installation	Rated Life Hours
Surface Mounted	30,000 - 50,000H
CRI	Colors
≥90	■ Black □ White
Input Voltage	Material
220V AC (Via the Built In Driver)	Powder Coated Aluminum.

TRACK MOUNTED ADJUSTABLE SPOT LIGHT


ACU TL 244010



Wattage	Beam Angle
7W	15° 24° 38°
Color Temperature	Lumen Output
3000k	531 Lm
Installation	Rated Life Hours
Track Mounted	30,000 - 50,000H
CRI	Colors
≥90	■ Black □ White
Input Voltage	Material
220V AC (Via the Built In Driver)	Powder Coated Aluminum.

TRACK MOUNTED SPOT LIGHT


ACU TL 244011



Wattage	Beam Angle
15W	15° 24° 38°
Color Temperature	Lumen Output
3000k	1272 Lm
Installation	Rated Life Hours
Track Mounted	30,000 - 50,000H
CRI	Colors
≥90	■ Black □ White
Input Voltage	Material
220V AC (Via the Built In Driver)	Powder Coated Aluminum.

TRACK MOUNTED ADJUSTABLE SPOT LIGHT

ACU TL 244012



Wattage	Beam Angle
24W	15° 24° 38°
Color Temperature	Lumen Output
3000k	2117 Lm
Installation	Rated Life Hours
Track Mounted	30,000 - 50,000H
CRI	Colors
≥90	■ Black □ White
Input Voltage	Material
220V AC (Via the Built In Driver)	Powder Coated Aluminum.

